

# Pro-Fit® Series

## ELECTRIC SCISSOR LIFTS



**Longer Duty Cycles Keep  
You On the Job Longer**



**Quieter, Cleaner Operation  
for Indoor Work Areas**



**Application-Specific Tools to  
Do Your Best Work**

**1930ES  
2030ES  
2630ES  
2646ES  
3246ES**

**[www.jlg.com](http://www.jlg.com)**



**JLG®**

**The Power To Do More**



# ***The Perfect Fit for Professionals on Any Job***

JLG Pro-Fit Series electric scissor lifts are the perfect fit for professional contractors.

Pro-Fit Series scissor lifts provide more of what you need on every job. More duty cycles to keep you on the job longer. More flexibility to work in a wide variety of environments with cleaner, quieter operation. And more features and productivity-enhancing tools matched to your profession. The Pro-Fit Series defines professional level performance and quality. From the super efficient electric drive to the integrated component set that helps reduce scheduled service requirements and operating costs. Never before has a series of scissor lifts delivered so much power and versatility for both indoor and outdoor applications.





# Pro-Fit Series



## **Pro-Fit Series Advantages:**

- Double the duty cycles
- Lowest cost of ownership
- Cleaner, quieter operation
- Exclusive application-specific accessories
- Larger platforms and higher capacities
- Three 30 in. (76 cm) wide models fit through narrow doorways and aisles
- Automatic posi-traction
- Durable, non-skid aluminum deck
- More loading options — fork from side or rear, drive onto trucks
- Variable degree tilt sensing



The Pro-Fit Series offers the most popular machine sizes, performance features and capabilities demanded by users and provides powerful productivity at an economical price.



# Works Longer & Harder...



## ■ Exclusive Power System Helps You Pull Double Duty

With a super efficient electric drive, the Pro-Fit Series provides measurably longer work cycles than any other electric scissor lift on the market.

## ■ Higher Capacities & Larger Platforms

The Pro-Fit Series can handle up to 1,000 lb (450 kg) on large 44 in. x 98.5 in. (1.12 m x 2.5 m) main platforms and up to 250 lb (113 kg) on 50 in. (1.27 m) extensions.

## ■ One-Handed Operation

Proportional drive and lift (up and down) controls provide a more natural position for better control and ease of operation.



## ■ Dual Capacities

Models 2630ES and 3246ES provide dual capacity. Push button selectable zones raise capacity at lower platform height.



## ■ Fit Through Narrow Aisles and Doorways

Three narrow 30 in. (76 cm) chassis models provide an unprecedented amount of clearance through doorways and down tight aisles.



## ■ Industry Best Mobility

Front-wheel drive and front-wheel steering offer tight turning circles for superior traction and maneuverability. And with a 5 in. (12.7 cm)\* ground clearance the Pro-Fit Series travels easier over doorway thresholds and allows drive-on loading for trailers and roll-back trucks.

\*3.5 in. (8.8 cm) on certain models



## Pro-Fit Narrow Models

- More narrow models with platform heights from 19 to 26 ft (6 to 8 m)
- More clearance through doorways and aisles with 30-inch wide chassis
- More maneuverability with a tight turning radius
- More convenience with easier to use fold-down rails\*
- More flexibility and productivity with available accessories

\*Standard on 2030ES and 2630ES

## Pro-Fit Wide Models

- More platform capacity up to 1,000 lb (454 kg)\*
- More reach with platform heights to 32 ft (9.75 m)
- More workspace with wider decks and platform extensions
- More productivity with pipe racks, panel carriers and other accessories

\*Dual rating on 3246ES 700/1,000 lb (318/454 kg)

# Cleaner & Quieter...

## ■ Lower Noise Levels

The Pro-Fit Series electric drive ensures quieter operation for more sound-sensitive areas and applications such as office buildings, shopping malls, museums and schools.



## ■ Fold-Down Handrails

Standard on four models including the compact Model 2030ES which allows access through doorways as low as 71.5 inches (1.82 m).




## ■ Skid-Resistant Deck

Built from corrosion resistant, high quality aluminum, the new JLG deck features non-skid strips for less slip and more grip for the operator.

## ■ Smarter Design Reduces Operating Costs

Integrated lift cylinder, valve, pump, motor and reservoir require only two hoses and four fittings, improving reliability, reducing scheduled service requirements and increasing profits.

Integrated motor, gearbox, spindle and brake facilitate service and troubleshooting while providing optimum power and performance.



## ■ Easy Access

Slide-out steel battery trays are one of many features to facilitate servicing.

## Quick Comparison

	Pro-Fit Series	Terex	Skyjack™
<b>Duty Cycles:</b>			
19-foot models	151	80	74
26-foot narrow models	97	41	50
<b>Fittings:</b>	4	39	44
<b>Hoses:</b>	2	18	22
<b>Accessories:</b>	Quik Welder®	n/a	n/a
	Pipe Rack	Pipe Rack	n/a
	Workstation	n/a	n/a
	Panel Rack	n/a	n/a

# With the Right Tools for the Job

## Optional Workstation in the Sky® Accessory Packages:

- Electrician's Package
- Plumber's Package
- Plant Maintenance Package
- Panel Carrier Accessory<sup>1</sup>
- Pipe Rack Accessory<sup>1</sup>
- Quik Welder® Package
- JLG Workstation

1. Not available on the 1930ES



These productivity-enhancing packages are designed for the specific needs of electricians, plumbers, mechanical contractors, drywall contractors and plant maintenance professionals. The packages include combinations of several of the following accessories: A workstation with workbench that holds a reciprocating saw, drill, circular saw, battery charger, components and an optional 12-Volt plug to power tool chargers from the scissor lift batteries. Other packaged features include a rail mounted vice, pipe racks, wire spool holder, panel carrier and Quik Welder system.



# Pro-Fit Series Specifications

## Model 1930ES

## Model 2030ES

## Model 2630ES

## Model 2646ES

## Model 3246ES

### Dimensional Data\*

<b>Platform Height – Elevated</b>	18 ft 9 in. (5.72 m)	20 ft (6.10 m)	25 ft 6 in. (7.77 m)	26 ft (7.92 m)	31 ft 9 in. (9.68 m)
<b>– Lowered</b>	34 in. (0.86 m)	43.5 in. (1.10 m)	48.5 in. (1.23 m)	49.5 in. (1.26 m)	49.5 in. (1.26 m)
<b>Platform Railing Height</b>	43.3 in. (1.10 m)	43.3 in. (1.10 m)	43.3 in. (1.10 m)	43.3 in. (1.10 m)	43.3 in. (1.10 m)
<b>Overall Height</b>	6 ft 5 in. (1.98 m)	7 ft 2.8 in. (2.20 m)	7 ft 7.8 in. (2.33 m)	7 ft 8.8 in. (2.36 m)	7 ft 8.8 in. (2.36 m)
<b>– With Rails Folded</b>	n/a	5 ft 11.5 in. (1.80 m)	6 ft 4.5 in. (1.94 m)	6 ft 5.5 in. (1.97 m)	6 ft 5.5 in. (1.97 m)
<b>Platform Dimensions</b>	30 in. x 73.5 in. (0.76 m x 1.87 m)	30 in. x 90.5 in. (0.76 m x 2.3 m)	30 in. x 90.5 in. (0.76 m x 2.3 m)	44 in. x 98.5 in. (1.12 m x 2.5 m)	44 in. x 98.5 in. (1.12 m x 2.5 m)
<b>– Platform Extension</b>	35.5 in. (0.9 m)	35.5 in. (0.9 m)	35.5 in. (0.9 m)	50 in. (1.27 m)	50 in. (1.27 m)
<b>Overall Machine Length</b>	6 ft 1.5 in. (1.87 m)	7 ft 6.5 in. (2.3 m)	7 ft 6.5 in. (2.3 m)	8 ft 2.5 in. (2.5 m)	8 ft 2.5 in. (2.5 m)
<b>– With Rails Folded</b>	n/a	9 ft 1.5 in. (2.78 m)	9 ft 1.5 in. (2.78 m)	9 ft 9.5 in. (2.98 m)	9 ft 9.5 in. (2.98 m)
<b>Overall Machine Width</b>	30 in. (76 cm)	30 in. (76 cm)	30 in. (76 cm)	46 in. (1.17 m)	46 in. (1.17 m)
<b>Wheelbase</b>	5 ft 3 in. (1.6 m)	6 ft 2 in. (1.88 m)	6 ft 2 in. (1.88 m)	6 ft 10 in. (2.09 m)	6 ft 10 in. (2.09 m)
<b>Ground Clearance</b>	3.5 in. (8.8 cm)	3.5 in. (8.8 cm)	3.5 in. (8.8 cm)	5 in. (12.7 cm)	5 in. (12.7 cm)
<b>Tire Size, (Non-Marking Solid)</b>	12.5 in. x 4 in. (31.8 cm x 10 cm)	16 in. x 5 in. (40.6 cm x 12.5 cm)	16 in. x 5 in. (40.6 cm x 12.5 cm)	16 in. x 5 in. (40.6 cm x 12.5 cm)	16 in. x 5 in. (40.6 cm x 12.5 cm)

### Performance Data

<b>Platform Capacity (ANSI)</b>	500 lb (227 kg)	800 lb (363 kg)	500/800 lb (227/363 kg)	1,000 lb (454 kg)	700/1000 lb (318 /454 kg)
<b>– Capacity On Deck Extension</b>	250 lb (113 kg)	250 lb (113 kg)	250 lb (113 kg)	250 lb (113 kg)	250 lb (113 kg)
<b>Lift/Lower Time</b>	22/28 seconds	30/30 seconds	40/40 seconds	40/40 seconds	50/50 seconds
<b>Maximum Drive Height</b>	18 ft 9 in. (5.72 m)	20 ft (6.10 m)	25 ft 6 in. (7.77 m)	26 ft (7.92 m)	31 ft 9 in. (9.68 m)
<b>Gross Vehicle Weight (ANSI/CSA)</b>	2,750 lb (1,247 kg)	3,750 lb (1,700 kg)	4,750 lb (2,155 kg)	4,770 lb (2,163 kg)	4,780 lb (2,168 kg)
<b>Ground Bearing Pressure</b>	109 psi (7.66 kg/cm <sup>2</sup> )	81 psi (5.69 kg/cm <sup>2</sup> )	90 psi (6.32 kg/cm <sup>2</sup> )	87 psi (6.11 kg/cm <sup>2</sup> )	87 psi (6.11 kg/cm <sup>2</sup> )
<b>Drive Speed, Lowered</b>	3.0 mph (4.82 kmph)	2.75 mph (4.43 kmph)	2.75 mph (4.43 kmph)	2.5 mph (4.00 kmph)	2.5 mph (4.00 kmph)
<b>Drive Speed, Elevated</b>	0.5 mph (0.8 kmph)	0.5 mph (0.8 kmph)	0.5 mph (0.8 kmph)	0.5 mph (0.8 kmph)	0.5 mph (0.8 kmph)
<b>Gradeability</b>	25%	25%	25%	25%	25%
<b>Turning Radius (Inside)</b>	0	0	0	0	0
<b>Turning Radius (Outside)</b>	69 in. (1.75 m)	81 in. (2.06 m)	81 in. (2.06 m)	95.1 in. (2.41 m)	95.1 in. (2.41 m)

### Power System/Chassis

<b>Batteries</b>	4 x 6V, 220 amp-hr	4 x 6V, 220 amp-hr†	4 x 6V, 220 amp-hr†	4 x 6V, 220 amp-hr†	4 x 6V, 220 amp-hr†
<b>Charger</b>	20 Amp Automatic (120V/240V–50/60HZ)	20 Amp Automatic (120V/240V–50/60HZ)	20 Amp Automatic (120V/240V–50/60HZ)	20 Amp Automatic (120V/240V–50/60HZ)	20 Amp Automatic (120V/240V–50/60HZ)
<b>Pump</b>	Fixed Clearance Gear	Fixed Clearance Gear	Fixed Clearance Gear	Fixed Clearance Gear	Fixed Clearance Gear
<b>Hydraulic Reservoir</b>	1.25 gal (4.73 L)	1.25 gal (4.73 L)	1.25 gal (4.73 L)	1.7 gal (6.4 L)	1.7 gal (6.4 L)
<b>Brakes (On Drive Wheels)</b>	Electric, Friction	Electric, Friction	Electric, Friction	Electric, Friction	Electric, Friction
<b>Rail Type</b>	Fixed	Fold Down	Fold Down	Fold Down	Fold Down
<b>Drive</b>	24V Electric (8 hp)	24V Electric (8 hp)	24V Electric (8 hp)	24V Electric (8 hp)	24V Electric (8 hp)

\* Certain weights and dimensions may vary due to options and to compliance with country standards.

† Optional 4 x 6V, 245 amp-hr

## The JLG “1 & 5” Warranty

JLG Industries, Inc. backs its products with its exclusive “1 & 5” Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.6-1999, and CSA Standard B354.2-01, as originally manufactured for intended applications.

## JLG Industries, Inc.

An Oshkosh Corporation Company

1 JLG Drive, McConnellsburg, PA 17233-9533

Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT

Fax 717-485-6417

www.jlg.com



Printed in USA  
FORM NO.: SS-ES-0704-10M  
PART NO.: 3131308  
R020705

**The Power To Do More**